Results for the 14'x120' circular tank with ramp:

Circular tank:

Tank Diameter = 120 ft Tank Wall thickness = 10 in (actual) Tank Height = 14 ft $f_y = 60,000 \text{ psi}$ $f'_c = 4,000 \text{ psi}$

Harimantal Ctaal 45 vahar				
Horizontal Steel = #5 rebar				
_ "		Distance from		
Bar#	Spacing (in)	finished floor (ft - in)		
1	3	0' 3"		
2	10	1' 1"		
3	10	1' 11"		
4	8	2' 7"		
5	8	3' 3"		
6	6	3' 9"		
7	6	4' 3"		
8	6	4' 9"		
9	6	5' 3"		
10	6	5' 9"		
11	6	6' 3"		
12	6	6' 9"		
13	6	7' 3"		
14	6	7' 9"		
15	6	8' 3"		
16	6	8' 9"		
17	8	9' 5"		
18	8	10' 1"		
19	8	10' 9"		
20	10	11' 7"		
21	10	12' 5"		
22	10	13' 3"		
23	6	13' 9"		

Vertical Steel = #5 @ 8" O.C.

Dowels "L" bars from tank to footing shall be #5 @ 8" O.C. 30" vertical leg, 8" horizontal leg

In the tank wall, at the corner of the notch for the ramp add:

- 4-#6 bars x 7'-10" long @ 4" O.C. vertically
- 4-#6 bars x 20' long @ 4" O.C. horizontally 4-#6 bars x 6' long @ 4" O.C. at a 45 degree angle.

		Designed PA NRCS 12/01
A NIDCC		Drawn <i>Hartz</i> 2/1/08
		Revisions <u>Pereverzoff</u> 1/9/08
	County, PA	
Natural Resources Conservation Services	ROUND TANK W/RAMP	Checked
United States Department of Agriculture	DETAIL Page 6.28	
	DETAIL Tuge 0.20	Approved